



## Features

- 4U rackmount design, meets EIA RS-310C Class
- Front panel with lock, Chassis cover with lock
- Removable filter
- Installation without tools
- Controls: Power ON/OFF button , system reset switch
- Indicators:Power ON/OFF ,HDD
- Smooth border prevent lacerating your skin

## Specification

Construction	Heavy duty steel ,Meets FCC/CE Class
Disk Drive Bays	Supports six(optional) 3.5" drives and three 5.25"drives
Cooling Fan	One 12cm and 8cm (optional) filter-fan at front panel
Passive Options	Backplane PBP-14P4/PBP-14P10/PBP-08P4/PBP-09P6/PBP-14L/PBP-15P12/PBP-15P7
Power Supply Options	AT/Redundant Power supply
Standard Color	Beige / Black
Dimensions ( W x D x H )	483mm * 577mm * 177mm
Operating Temperature Range	0??C-55??C(0??C-70??C non-operating)
Relative Humidity	5% to 95%,non-condensing
Vibration ( operating )	5 to 15Hz , 0.1"double-amplit. Displacement, 15 to 150 Hz,1.5G acceleration peak to peak
Shock ( operating )	10G acceleration peak (11ms duration)
More Information	USB connector at front panel, Panel Fasteners

# Dimension Diagram

