



Features

- Supports Pentium® 4 / Celeron® D processors ,LGA 775 socket
- Intel® 865G chipset, Up to 4GHz, 533/800MHz FSB
- DDR DIMM x 2, max. 2GB
- Integrated 82865G VGA, shared memory up to 64M , CRT support
- Integrated two 10/100 BaseT and optional two Gigabit LAN
- Watchdog timer, PCI to ISA bridge, ISA high drive
- 2x SATA, 4x USB 2.0
- Intel Hyper-threading technology support
- RAID optional

Specification

CPU ?Intel® Pentium® 4, Celeron® D processor/LGA 775(FSB 533MHz / 800MHz)

Chipsets ?Intel 865GV

Memory ?Two DDR sockets support up to 2GB DDR SDRAM PC333/400 DDR SDRAM, without ECC

BIOS ???Award 4MB

Display ??????Integrated in intel 865 GV

Dynamic share system memory up to? 64MB

Capability to drive? CRT(VGA/SVGA/XGA/SXGA)

Resolution up to? 2048*1536(32bpp,85Hz)

Ethernet ??INTEL 82562EM 10/100BASE-T,INTEL 82547EI 10/100/1000BASE-T

RJ45 connector with LED indicator

Two Gigabyte LAN optional

Audio ???Realtek ALC 202A /ALC 655 (AC'97)

EIDE ??????Support four IDE devices by two EIDE interfaces with ATA 100/66/33

SATA ???Support two SATA devices with two SATA interface up to 150MB/s

I/O???? ?Two serial ,one parallel, one FDD, four USB 2.0 ,two ports on bracket for keyboard&mouse

RAID (optional)?? ??INTEL 82801ER

Hardware Monitoring? System monitor(fan,temperature,voltage)

Watchdog Timer????? ??256-level time-out intervals, supports RESET/NMI

Power Requirement? ?AT/ATX +5V ±5%,+12V ±5%

Dimension????????? 338mm×122mm (L×W)

Environmental????? Operating Temperature:0-60℃

Storage Temperature:-20-80℃

Relative Humidity:5%--90%, non-condensing

GW ???1kg

Order information

Model	RAID	Video	VGA	10/100Mbps Ethernet	GbE
NOVO-7865LGV-N	None	1	1	1	0
NOVO-7865LGV-GN	None	1	1	1	1
NOVO-7865LGV-NR	Yes	1	1	1	0
NOVO-7865LGV-GNR	Yes	1	1	1	1