



# BBS-300

3U Rackmount Chassis



## Features

- MI-965GM
- Intel® Socket 479 Core 2 Duo Mobile
- Supports DDR2 SO-DIMM Memory, up to 4GB
- Intel GME965 + ICH8M
- Mobile Intel X3100
- Support 10 x USB2.0, 3 x SATA, 1 x CF, 2 x RS-232



## System

<b>CPU</b>	Intel Socket 479 Core 2 Duo Mobile
<b>Memory</b>	Supports DDR2 SO-DIMM Memory, up to 4GB
<b>Chipset</b>	Intel GME965 + ICH8M, 533/800MHz FSB
<b>Watchdog</b>	1-255s/m, Watchdog

## Graphics

<b>Controller</b>	Mobile Intel X3100
<b>Output</b>	Support DVI, LVDS, DVI to VGA, TV-OUT, S-VIDEO
<b>Resolution</b>	VGA up to 2048 x 1536

## Ethernet

<b>Controller</b>	2 x Marvell 88E8055
<b>Connector</b>	RJ-45

## Power

<b>Type</b>	ATX
-------------	-----

## I/O

<b>Serial Port</b>	2 x RS-232 ports
<b>USB</b>	6 x USB2.0
<b>LVDS</b>	1 x LVDS
<b>IDE</b>	1 x IDE
<b>CF</b>	1 x CF
<b>PCI</b>	1 x PCI

## Back I/O

<b>VGA</b>	1 x VGA
<b>KB/MS</b>	1 X Mini-Din connector for KB & MS (PS/2 standard via Y-cable)
<b>S-VIDEO</b>	1 x LVDS
<b>DVI</b>	1 x DVI
<b>AV</b>	1 x AV

## Parameter

<b>Operating Temp</b>	0 ~ 60° C (32 ~ 140° F)
<b>Operating Humidity</b>	10 ~ 95% RH @40° C (non-condensing)
<b>Dimension</b>	447 x 300.5 x 132.5mm (17.6" x 11.8" x 5.3")

## BBS-300 Composition

